

EKF 423 U

FORNO ELETTRICO VENTILATO A CONVEZIONE
CON UMIDIFICAZIONE

ELECTRIC CONVECTION OVEN WITH HUMIDIFICATION



CARATTERISTICHE DIMENSIONALI

Dimensioni Forno (LxPxH mm)	590	695	590
Peso (kg)	34,2		
Passo guide (mm)	74		

DIMENSIONAL FEATURES

Oven dimensions (WxDxH mm)	590	695	590
Oven weight (kg)	34,2		
Distance between rack rails (mm)	74		

CARATTERISTICHE ELETTRICHE

Potenza elettrica (kW)	2,8
Frequenza (Hz)	50/60
Voltaggio (Volt)	AC 220/230
N° Motori	1 Monodirezionale
Generatore di vapore (boiler)	/
Protezione acqua	IPX3

ELECTRICAL FEATURES

Power supply (kW)	2,8
Frequency (Hz)	50/60
Voltage (Volt)	AC 220/230
N° of motors	1 Unidirectional
Boiler	/
Protection against water	IPX3

CARATTERISTICHE FUNZIONALI

Alimentazione	Elettrico
Capacità	N° 4 teglie (429x345 mm)
Cottura	Ventilata
Umidificazione	Indiretta a pulsante
Camera di cottura	Acciaio AISI 430
Temperatura	50 - 300 °C
N° Programmi	/
Fasi programmabili	/
Temperatura preimpostata	/
Preiscaldamento	/

FUNCTIONAL FEATURES

Power	Electricity
Capacity	N° 4 trays (429x345 mm)
Type of cooking	Ventilated
Humidification	Indirect with button
Cooking chamber	AISI 430 Stainless steel
Temperature	50 - 300 °C
N° of programs	/
Programmable cooking steps	/
Pre-heating temperature	/
Pre-heating function	/

DOTAZIONI DI SERIE

Supporti Laterali	1dx + 1sx
Vassoio in alluminio (429x345 mm)	4pz
Cavo	Monofase [2G 1,5] - L=1350 mm

EQUIPMENT

Lateral supports	1right + 1left
Aluminum trays (429x345 mm)	4 pcs
Cable	Single-phase [2G 1,5] - L=1350 mm

